



Model: EOLC
(Exhaust Only Low Ceiling)

General Specifications:

Hood shall be standard straight exhaust only type. Hood shall be manufactured with a short front to maintaining adequate clearance. The hood shall be fabricated from Type 430 stainless steel with #3 or #4 polish on all exposed surfaces.

Hood shall be construction with seams and joints welded and sealed liquid tight, to conform to NFPA 96. Corners of hood shall be trimmed to give the hood a straight, crisp appearance free of warps. Grease filters shall be UL classified, non-clogging, baffle type. Filter size and quantity to extend the full length of hood and shall be easily removable for cleaning purposes.

All exhaust plenum surfaces and filters shall drain into a removable grease trough and be conveyed to a removable grease container for easy cleaning. Exhaust collar shall have a 3/4" welding flange for easy field connection.

Complete computer generated submittal drawings including material type, hood section view(s), plan view(s) and options chosen shall be provided. Duct sizes, CFM requirements and static pressures shall be shown on drawings. The hood shall bear the NSF Seal of Approval. Hood to be manufactured by LARKIN INDUSTRIES, INC. 1-800-322-4036

Optional Features:

- Electrical controls (Remote Only)
- Fire protection system (Wall Mounted Only)
- Enclosure panels
- End panels
- Wall splash panels